


IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF EXPRESS MAILING

I hereby certify that this paper and the documents and/or fees referred to as attached therein are being deposited with the United States Postal Service on April 23, 2001 in an envelope as "Express Mail Post Office to Addressee" service under 37 CFR §1.10, Mailing Label Number EL580401026US, addressed to the Commissioner for Patents, Washington, DC 20231.


Aurelia Sanchez

Attorney Docket No.: MES1P041

First Named Inventor: Kineo MATSUI

TRANSMITTAL LETTER FOR A PCT INTERNATIONAL APPLICATION ENTERING THE NATIONAL STAGE IN THE U.S. AS A DESIGNATED or ELECTED OFFICE UNDER 35 USC 371

Commissioner for Patents
Box PCT
Attention: DO/EO
Washington, DC 20231

Transmitted herewith are the papers required to enter the national stage in the U.S. as a designated office/elected office for the following PCT international patent application:

INTERNATIONAL APPLICATION NUMBER: PCT/JP99/05924

Int'l Filing Date: October 26, 1999

1st Priority Date: October 27, 1998

Inventor(s): Kineo MATSUI

For: METHOD OF EMBEDDING DIGITAL WATERMARK AND METHOD OF DECODING EMBEDDED DIGITAL WATERMARK

The United States Patent Office is: (select one)

- ☒ A Designated Office (No Demand was filed - See 37 CFR 1.494)
☐ An Elected Office (A Demand for Preliminary Examination was Filed - See 37 CFR 1.495)

Enclosures:

- ☐ A copy of the international application (if this line is not checked, the international application was previously communicated by the International Bureau or the international application was originally filed in the USPTO).
☒ An English Translation of the International Application
☐ A Combined Declaration and Power of Attorney
☐ A copy of amendments made under PCT Article 19
☐ A translation of amendments made under PCT Article 19
☐ A translation of amendments made under PCT Article 34 (annexes to the international preliminary examination report)
☐ Information Disclosure Statement

09/830236

JC18 Rec'd PCT/PTO 2 3 APR 2001

- ☐ An Assignment of the Invention to:
(with \$40.00 recordal fee)
- ☐ A Preliminary Amendment
- ☒ A copy of the International Search Report
- ☐ A copy of the Preliminary Examination Report

Fee Calculation:

<input type="checkbox"/>	Applicant is entitled to Small Entity Status under 37 C.F.R. §1.27.	
<input checked="" type="checkbox"/>	BASIC FEE	\$860.00
	(IPEA-U.S. \$690/345; ISA-U.S. \$710/355; PTO not ISA or IPEA \$1000/500; U.S. IPEA all claims meet 33(2)-(4) \$100/50; File w/ EPO or JPO search report \$860/430;)	
<input type="checkbox"/>	Surcharge for filing a late oath or declaration (\$130/65)	\$
<input type="checkbox"/>	Surcharge for filing a late translation (\$130)	\$
<input type="checkbox"/>	Assignment recordal fee (\$40)	\$
<input type="checkbox"/>	Multiple dependent claims (\$270/135)	\$
<input checked="" type="checkbox"/>	Excess claims - see calculation below	\$
Total Claims:	08- 20 = 00	X \$18/9 claim = \$
Independent Claims:	04- 3 = 01	X \$80/40 ind. claim = \$80.00
		Excess Claim Total \$80.00
		TOTAL FEES \$940.00

☒ Check No. 10993 in the amount of \$940.00 is enclosed cover the filing fees (including the basic national fee under 37 CFR 1.492(a)) as calculated above.

☒ The Commissioner is authorized to charge any fees beyond the amount enclosed which may be required, or to credit any overpayment, to Deposit Account No. 500388 (Order No. MES1P041).

General Authorization for Petition for Extension of Time (37 CFR §1.136)

☒ Applicants hereby make and generally authorize any Petitions for Extensions of Time as may be needed for any subsequent filings. The Commissioner is also authorized to charge any extension fees under 37 CFR §1.17 as may be needed to Deposit Account No. 500388 (Order No. MES1P041).

☒ Please send correspondence to the following address:

Customer Number 022434
BEYER WEAVER & THOMAS, LLP
 P.O. Box 778
 Berkeley, CA 94704-0778
 Telephone (650) 961-8300
 Fax (650) 961-8301



Date: April 23, 2001

Steve D Beyer
 Steve D Beyer
 Registration No. 31,234

8/PRTS

09/830236

JC18 Rec'd PCT/PTO 23 APR 2001

SPECIFICATION

METHOD OF EMBEDDING DIGITAL WATERMARK AND METHOD OF DECODING

EMBEDDED DIGITAL WATERMARK

5 Technical Field

The present invention relates to a method of embedding a digital watermark to prevent unauthorized copies of an original color image as well as a method of decoding the embedded digital watermark.

10

Background Art

The advanced computer network like the Internet accelerates digitalization of information and allows a large number of users to access required information readily. Such an advanced environment, on the other hand, causes digital contents including digital information with the copyright to be readily duplicated as unauthorized copies without permission of copyright holders. Infringement of the copyright due to the illegal copies is becoming a significant problem. With a view to preventing the infringement of the copyright with regard to color images, which are the main part of digital information in the digital contents, the digital watermarking technique draws the vigorous attention. The digital watermarking technique embeds the copyright information in data of an original color image in a secret and unnoticeable manner to any third person and extracts the copyright information from the embedded original color image according to the requirements.

A large number of technical suggestions have been made for digital watermarking of monochromatic images. The luminance signal (the Y signal) of a color image can be processed like the monochromatic image. The prior art technique accordingly embeds the digital watermark in the luminance signal of the color image corresponding to the monochromatic image.

There have been no proposed techniques that embed a digital watermark by utilizing signals and data intrinsic to color images. The proposed digital watermark embedding techniques are described in 'Deep-layered Information Recording in Color Images' that utilizes the color space of a color printer (the Institute of Image Electronics Engineers of Japan, the Proceedings of Annual Conference 7, 20, pp.47-48), 'One Technique of Color Watermarking by Taking into Account Visual Characteristics' that is constructed as a model taking advantage of visual characteristics (IMPS 97, I-3.14, pp.45-46 (1997)), and 'One Technique of Embedding Digital Watermark in Digital Image' (SITA 97, Vol. 2, pp.541-544 (1997)). These prior art techniques, however, have drawbacks such that the model and the digital watermark embedding process are rather complicated. It has also been pointed out that the method of embedding the digital watermark in lower bits of the color image undesirably deteriorates the picture quality of the resulting color image.

The object of the present invention is thus to provide an improved method of embedding and decoding a digital watermark, which takes advantage of characteristics intrinsic to color images, readily and securely embeds a digital watermark into an original

image without deteriorating the original image, and effectively maintains the digital watermark against clipping, JPEG compression, and other series of digital processing.

5 Disclosure of the Invention

The present invention is directed to a method of embedding digital watermark information in a color image. The method includes the steps of: providing a color signal transformation matrix and an inverse color signal transformation matrix, the color signal transformation matrix transforming image data in a first colorimetric system, which expresses a predetermined color space by a combination of plural parameters, into image data in a second colorimetric system, which expresses the predetermined color space by a combination of other plural parameters, the inverse color signal transformation matrix carrying out inverse of the transformation; adjusting the color signal transformation matrix by either of adding and subtracting a digital watermark matrix to and from the color signal transformation matrix, the digital watermark matrix including an arbitrary numerical value of real number x , which represents the digital watermark information, as an entry thereof and satisfying a condition that a sum of respective entries in each row and in each column is all substantially equal to zero; transforming the image data in the first colorimetric system into image data in the second colorimetric system with the adjusted color signal transformation matrix; and inversely transforming the resulting image data in the second colorimetric system, which is

obtained by the transformation, into the image data in the first colorimetric system with the inverse color signal transformation matrix, so as to embed the digital watermark information into the color image.

5 There are a variety of known colorimetric systems that express a predetermined color space by a combination of plural parameters. A transformation matrix and an inverse transformation matrix are defined between each pair of different colorimetric systems. The technique of the present invention uses a color signal transformation matrix and an inverse color signal transformation matrix for the simple arithmetic operations discussed above and thereby embeds the digital watermark in each pixel while preventing deterioration of an original color image. The embedded digital watermark has a high resistance against clipping of an image, compression, and other series of digital processing.

10 Here an RGB colorimetric system using three primary colors of light as parameters and a YCbCr colorimetric system using a luminance signal and color difference signals as parameters may be applied appropriately for either of the first colorimetric system and the second colorimetric system. These colorimetric systems are often used for image data processing, and transformation matrices between these colorimetric systems are well known. There are accordingly a large number of retouching software for processing the image data in these colorimetric systems. These factors facilitate the process of embedding the digital watermark.

25 The arbitrary numerical value of real number x may be an

arbitrary value in a range of not less than -0.1 and not greater than 0.1. This restricts the effects on each entry of the color signal transformation matrix and thereby relieves the influence on the original color image. Such limitation of the numerical value of real number may reduce the effects on the original color image to be lower than the range of general visual recognition of human eyes.

In accordance with one preferable application, the embedding method further includes the step of: carrying out underflow correction or overflow correction to cause an arbitrary pixel value to be an integer within a predetermined range in the process of inversely transforming the digital information in the YCbCr colorimetric system, that is, the luminance signal and the color difference signals, which is obtained by the transformation with the digital watermark matrix, into the color signals in the RGB colorimetric system, that is, the three primary color signals of light, by means of the inverse color signal transformation matrix. Since the watermark information is added to the original image data, inverse transformation of the transformed luminance signal and color difference signals may cause the resulting image data to be out of the range of the original image data. The underflow correction or the overflow correction corrects the underflow or the overflow and causes the resulting image data, which has undergone the inverse transformation, to be within the allowable range of the original image data. For example, it is assumed that the original image is specified by 8-bit data with regard to each color R, G, and B

and 256 tones in the range of 0 to 255 is expressible with regard to each color. When the resulting value obtained by the inverse transformation is negative, the underflow correction is carried out to set the value '0' to the resulting value. When the resulting value exceeds 255, the overflow correction is carried out to set the value '255' to the resulting value.

The present invention is also directed to a decoding method to take a digital watermark out of image data with the digital watermark embedded therein. The method includes the steps of:

10 calculating a difference matrix between watermark-embedded data, which is obtained by transforming a color image with a digital watermark embedded therein into color signals in a YCbCr colorimetric system, that is, a luminance signal and color difference signals, and watermark-free data, which is obtained by

15 transforming an original image without the digital watermark embedded therein into color signals in the YCbCr colorimetric system, that is, a luminance signal and color difference signals; decomposing the difference matrix into respective rows and calculating an arbitrary numerical value of real number x , which

20 is supposed to represent the digital watermark information, with regard to each row; and estimating a mean of the numerical values of real number x calculated with regard to the respective rows as the digital watermark information.

This method enables the arbitrary numerical value of real number x , which represents the digital watermark information embedded in the luminance signal and the color difference signals,

to be decoded with a high accuracy. The original image is required for decoding. Whether the color image with the digital watermark embedded therein is widely available, it is impossible to decode the digital watermark from only the available color image.

5 It is preferable that the arbitrary numerical value of real number x , which is supposed to represent the digital watermark information, is calculated on the premise that an absolute value of a difference between entries in each row of the difference matrix is within a predetermined range. This arrangement further enhances
10 the accuracy of decoding the numerical value of real number x that represents the digital watermark. The significantly small absolute value diffuses the range of data and lowers the accuracy in estimation of the numerical value of real number x . The unnecessarily large absolute value, on the other hand, lowers the reliability while
15 decreasing the number of data and making the estimated value approach the embedded value. It is accordingly preferable that the absolute value is in a range of 3 to 10.

 The method of embedding the digital watermark and the method of decoding the embedded digital watermark may be attained in the
20 form of a storage medium, in which a program of the corresponding method is stored. Typical examples of the storage medium include CD-ROMs, memory cards, and flexible disks. Such programs may be downloaded via a communication line. The method of embedding the digital watermark may be incorporated in a retouching software for
25 processing image data integrally or as a plug-in software program. The embedding method and the decoding method may alternatively be

actualized by independent programs for embedding the digital watermark and decoding the embedded digital watermark. The color images delivered as the digital contents often undergo compression by a diversity of compression techniques like JPEG. The programs of the methods may thus be incorporated in the image data compression software integrally or as plug-in software programs. The programs may integrally be incorporated in a scanner that reads printed image data as digital data or scanning software. The programs may also be incorporated in a printer driver and a printer that print digital data.

Brief Description of the Drawings

Fig. 1 shows the principles of methods of embedding and decoding a digital watermark in a embodiment of the present invention;

Figs. 2(a) through 2(d) show digital color images with various values x embedded therein as digital watermark information according to the method of Fig. 1;

Fig. 3 is a flowchart showing a detailed algorithm of digital watermark embedding process;

Fig. 4 is a flowchart showing a detailed algorithm of digital watermark decoding process;

Figs. 5(a) through 5(d) are histograms of the watermark information x estimated from the image with the watermark information $x=0.1$, $x=0.05$, $x=-0.1$, and $x=-0.05$ embedded therein;

Fig. 6 shows an image with the watermark information $x=0.1$

embedded therein, which is subjected to various digital processing and attacks;

Figs. 7(a), 7(b), and 7(c) are histograms of the value x decoded from clipped image data1, data2 and data3;

5 Figs. 8(a), 8(b), and 8(c) are histograms of the value x decoded from compressed image data;

Fig. 9 is histogram of the value x decoded from image data exposed to StirMark attacking;

10 Figs. 10 (a) and 10(b) are histograms of the value x decoded from image data overwritten according to the identical algorithm; and

Fig. 11 is a block diagram schematically illustrating the structure of a digital watermark processor that carries out the digital watermark embedding process and the digital watermark
15 decoding process in the embodiment.

Best Modes of Carrying Out the Invention

One mode of carrying out the present invention is discussed below as a preferred embodiment.

20

<Principles of Embedding and Decoding Digital Watermark>

Fig. 1 shows the principles of a method of embedding a digital watermark in a digital color image and a method of decoding the embedded digital watermark in the embodiment. A digital color image
25 or an original image expressed in an RGB colorimetric system is defined as a set of a large number of pixels arranged in a matrix

specified by a horizontal resolution (hereinafter referred to as HSize) and a vertical resolution (hereinafter referred to as VSize). A color P' (where the mark ' denotes a matrix) of each pixel is defined as $P' = [r, g, b]^t$ (where the superscript t denotes a transposed matrix) using the densities of the respective color signals, red (r), green (g), and blue (b), which are the three primary colors of light, expressed by a predetermined resolving power (for example, 256 tones in a range of 0 to 255). One of the known systems for defining the color of each pixel other than the RGB colorimetric system is a YCbCr colorimetric system using a luminance signal and color difference signals. A color F' of each pixel in this colorimetric system is defined as $F' = [y, cb, cr]^t$.

These two colorimetric systems are not independent of each other, but are mutually transformable by a color signal transformation matrix A' and its inverse matrix A'^{-1} as shown in Equations (1) and (2) given below:

$$F' = A'P' \quad (1)$$

$$P' = A'^{-1}F' \quad (2)$$

where the matrix A' and the transposed matrix A'^t in Equations (1) and (2) are specified as follows in this embodiment:

$$A' = \begin{bmatrix} 0.299 & 0.587 & 0.114 \\ -0.169 & -0.331 & 0.500 \\ 0.500 & -0.419 & -0.081 \end{bmatrix}$$

$$A' = \begin{bmatrix} 1.000 & -0.001 & 1.402 \\ 1.000 & -0.344 & -0.714 \\ 1.000 & 1.772 & 0.001 \end{bmatrix}$$

The embodiment adopts the method that embeds digital watermark information x in the course of transforming a pixel P' in an original image expressed by the RGB colorimetric system into a pixel F' expressed by the YCbCr colorimetric system and inversely transforms the image with the embedded digital watermark information into the RGB colorimetric system.

One of the essential requirements in the process of embedding the digital watermark information is to minimize the deterioration of the picture quality by the embedded digital watermark. Here note the entries in the transformation matrix A' . The sum of the absolute values of the respective entries in each row is all equal to one. It is accordingly required to maintain the relationship that the sum of the absolute values of the respective entries in each row of the transformation matrix is all equal to one, in order to prevent the deterioration of the picture quality while transforming the pixel P' in the original image expressed by the RGB colorimetric system into the pixel F' expressed by the YCbCr colorimetric system. Namely it is desirable to keep the mutual relations of the entries in the course of embedding the digital watermark information in the transformation matrix A' . A watermark matrix X' given below is provided by taking into account such points:

$$X' = \begin{bmatrix} 0 & -x & x \\ x & 0 & -x \\ -x & x & 0 \end{bmatrix} \quad (3)$$

where x denotes watermark information and takes a numerical value of real number.

The procedure causes the color image to be subjected to digital watermarking with this watermark matrix X' . In other words, an arithmetic operation of Equation (4) is performed for a pixel of interest P' :

$$F'(X) = (A' + X')P' \quad (4)$$

This arithmetic operation is carried out for all the pixels, so as to complete embedding the digital watermark. The resulting $F'(X)$ signal is decoded according to Equation (5) given below with the inverse transformation matrix A^{-1} :

$$\begin{aligned} P'(X) &= A^{-1}F'(X) = A^{-1}(A'P' + X'P') \\ &= A^{-1}A'P' + A^{-1}X'P' \\ &= P' + A^{-1}X'P' \end{aligned} \quad (5)$$

Here $P'(X)$ corresponds to an RGB color signal with the watermark information x embedded therein. As clearly understood from Equation (5), the pixel vector $P'(X)$ is specified as the original signal P' with the noise $A^{-1}X'P'$, which includes the watermark information x , superposed thereon. Figs. 2(a) through 2(d) show

resulting images that have undergone the above transformation with various numerical values of real number x in a range of $-0.1 \leq x \leq 0.1$ as an example. The color slightly changes with a variation in value of the watermark information x . The luminance information is, however, well preserved, and the change of the color is continuous and gives no feeling of incompatibility as shown by the black and white images of Figs. 2(a) through 2(d). The change of the color is extremely little and does not deteriorate the picture quality of the original color image. The numerical value of real number x may be out of this range but may be determined appropriately by taking account of the accuracy of calculation.

While the data of the RGB signal is an integral number, the transformed data of the YCbCr signal according to Equation (1) is a real number and thus requires rounding to an integral number in the course of the YCbCr to RGB inverse transformation. The process of inversely transforming according to Equation (2) and rounding to an integer may result in underflow where the resulting pixel value becomes negative or in overflow where the resulting pixel value exceeds an upper limit. In order to solve such problems, the technique of the embodiment carries out underflow correction and overflow correction. The correction sets zero to any negative pixel value and sets an upper limit value (for example, 255) of the bit expression to any pixel value exceeding the upper limit value.

The following describes a process of decoding the watermark information x from the image $P'(X)$ with the digital watermark

embedded therein according to the procedure discussed above. The data P' of the original image is required for decoding the digital watermark information x from the image $P'(X)$.

5 Multiplying the image $P'(X)$ by a known color signal transformation matrix A gives a matrix H' according to Equation (6) given below:

$$\begin{aligned} H'(X) &= A'P'(X) = A'(P' + A^{-1}X'P') \\ &= A'P' + A'A^{-1}X'P' = A'P' + X'P' \end{aligned} \quad (6)$$

10 Here the signal F' obtained by transforming the original image with the matrix A' is subtracted from the matrix $H'(X)$. The resulting difference is expressed by Equation (7) given below:

$$15 \quad H'(X) - F' = (A'P' + X'P') - A'P' = X'P' \quad (7)$$

Where y_1 , y_2 , and y_3 denote the signals of the difference XP , the matrix is rewritten as Equation (8) given below:

$$X'P' = \begin{bmatrix} y_1 \\ y_2 \\ y_3 \end{bmatrix} = \begin{bmatrix} 0 & -x & x \\ x & 0 & -x \\ -x & x & 0 \end{bmatrix} \begin{bmatrix} r \\ g \\ b \end{bmatrix} \quad (8)$$

20 Decomposing this equation specifies the respective entries as shown in Equations (9) given below. The value x is then calculated from these entries according to Equations (10) given below:

$$\begin{aligned}
y_1 &= bx - gx \\
y_2 &= rx - bx \\
y_3 &= gx - rx
\end{aligned}
\tag{9}$$

$$\begin{aligned}
x_1 &= y_1/(b-g) \\
x_2 &= y_2/(r-b) \\
x_3 &= y_3/(g-r)
\end{aligned}
\tag{10}$$

In Equations (10), the denominator close to zero causes an arithmetic error in the calculation of the value x . There may also be some noise in the calculation. It is accordingly desirable to calculate the digital watermark information on the premise that the absolute value of each difference in Equations (10) is greater than a preset value (for example, 5). The significantly small absolute value diffuses the range of data and lowers the accuracy in estimation of the value x . The unnecessarily large absolute value, on the other hand, lowers the reliability while decreasing the number of data and making the estimated value approach the embedded value.

On the premise that this condition is fulfilled, the values (x_1, x_2, x_3) are determined according to Equations (10), and the mean x_{av} of these three values is calculated as:

$$x_{av} = (x_1 + x_2 + x_3) / 3$$

The calculated value x_{av} is specified as the estimated value of the watermark information x . The estimation of the watermark information x according to this procedure is carried out for each

pixel. The value having the greatest statistical probability is eventually determined as the watermark information x .

<Description of Algorithm of Embedding and Decoding Digital
5 Watermark>

Concrete algorithms of the method of embedding a digital watermark in a color image and the method of decoding the embedded digital watermark carried out in the embodiment are described in detail with referring to the flowcharts of Figs. 3 and 4.

10 The process of embedding the digital watermark is discussed first with the flowchart of Fig. 3. Density values of the R, G, and B signals of a set of pixels P (hereinafter may simply be referred to as the pixel) representing an original image are expressed as $R(i,j)$, $G(i,j)$, and $B(i,j)$. Here i denotes an integer in a range
15 of 1 to a dimension of the original image in the vertical direction (VSize), and j denotes an integer in a range of 1 to a dimension of the original image in the horizontal direction (HSize). The procedure first determines the value x , which represents the digital watermark information, and substitutes the value x into Equation
20 (3) to specify a watermark matrix X' (step S100). The procedure then substitutes the watermark matrix X' into Equation (4) and transforms the set of pixels P' in the original image into a set of pixels F' in the YCbCr colorimetric system. The luminance signal and the color difference signals of the pixel F'(X) are expressed
25 as $Y'(i,j)$, $Cb'(i,j)$, and $Cr'(i,j)$, which are calculated according to Equations (11) through (13) given below:

$$Y'(i,j) \leftarrow R(i,j)*0.299 + G(i,j)*(0.587-x) + B(i,j)*(0.114+x) \quad (11)$$

$$Cb'(i,j) \leftarrow R(i,j)*(-0.169+x) - G(i,j)*0.331 + B(i,j)*(0.5-x) \quad (12)$$

$$Cr'(i,j) \leftarrow R(i,j)*(0.5-x) + G(i,j)*(-0.419+x) - B(i,j)*0.081 \quad (13)$$

5

Transformation according to these Equations (11) through (13) is repeatedly carried out with regard to all the combinations of (i,j) (steps S110 and S120). This gives transformed data in the YCbCr colorimetric system representing an image with the digital watermark information x embedded therein.

10

The digital color image is generally expressed by the RGB colorimetric system, for example, on the computer. The procedure accordingly transforms the resulting F'(X) signal back to the RGB colorimetric system with the inverse transformation matrix A^{-1} , and carries out the underflow correction or the overflow correction to make the value of each pixel integral (step S130).

15

Such correction is attained by the series of processing shown below. The procedure first calculates the R signal by the following calculation of the respective signals. When the obtained R signal is less than zero, the correction sets the value '0' to the R signal. When the obtained R signal is greater than 255, the correction sets the value '255' to the R signal. The similar series of processing is carried out with regard to the other color signals G, and B.

20

$$R'(i,j) \leftarrow Y'(i,j)*1.0 - Cb'(i,j)*0.001 + Cr'(i,j)*1.402$$

25

$$\text{if } R'(i,j) < 0, \text{ then } R'(i,j) \leftarrow 0$$

$$\text{else if } R'(i,j) > 255, \text{ then } R'(i,j) \leftarrow 255$$

$G'(i,j) \leftarrow Y'(i,j)*1.0 - Cb'(i,j)*0.344 - Cr'(i,j)*0.714$

if $G'(i,j) < 0$, then $G'(i,j) \leftarrow 0$

else if $G'(i,j) > 255$, then $G'(i,j) \leftarrow 255$

5

$B'(i,j) \leftarrow Y'(i,j)*1.0 + Cb'(i,j)*1.772 + Cr'(i,j)*0.001$

if $B'(i,j) < 0$, then $B'(i,j) \leftarrow 0$

else if $B'(i,j) > 255$, then $B'(i,j) \leftarrow 255$

10 The processing of step S130 is carried out repeatedly with regard to all the combinations of (i,j) (step S140). This gives the resulting data in the RGB colorimetric system that represents the image with the digital watermark information x embedded therein.

The following describes the process of decoding the digital watermark information x from the digital color image with the watermark information x embedded therein. One example of the decoding process is shown in the flowchart of Fig. 4. When the program enters this processing routine, the procedure first determines whether or not the values in the RGB colorimetric system are integers in the range of 1 to 254 as expressed below (step S200). This determines whether or not each pixel of interest has a sufficient reliability to be used for decoding the watermark information x . In the case where the value is equal to either 255 or 0, the overflow correction or the underflow correction carried out in the digital watermark embedding process discussed above may cause an overflow error or an underflow error.

15

20

25

If ($R'(i,j)$, $G'(i,j)$, or $B'(i,j)$) = (0 or 255),
else go to step S250

5 When the pixel of interest satisfies this condition, the
procedure determines whether or not the other condition is fulfilled.
Namely it is determined whether or not the absolute value of the
difference in each corresponding pixel of the original image is
greater than a predetermined value (5 in the algorithm of this
10 embodiment) (step S210). The processing of this step is expressed
as:

If the absolute value of ($B(i,j)-G(i,j)$, $R(i,j)-B(i,j)$, or
 $G(i,j)-R(i,j)$) > 5,
15 else go to step S250

The procedure carries out the conversion into the YCbCr
colorimetric system according to equations given below with regard
to the respective pixels of the original image as well as the
20 respective pixels with the embedded digital watermark information
that satisfy both the two conditions described above (step S220).
Here Y, Cb, and Cr denote the luminance signal Y and the color
difference signals Cb and Cr obtained by transforming the pixels
of the original image into the YCbCr colorimetric system. Y' ,
25 Cb'' , and Cr'' denote the luminance signal Y and the color difference
signals Cb and Cr obtained by transforming the pixels with the

embedded digital watermark information x into the YCbCr colorimetric system.

5 $Y(i,j) \leftarrow R(i,j)*0.299 + G(i,j)*0.587 + B(i,j)*0.114$
 $Cb(i,j) \leftarrow -R(i,j)*0.169 - G(i,j)*0.331 + B(i,j)*0.5$
 $Cr(i,j) \leftarrow R(i,j)*0.5 - G(i,j)*0.419 - B(i,j)*0.081$

10 $Y''(i,j) \leftarrow R'(i,j)*0.299 + G'(i,j)*0.587 + B'(i,j)*0.114$
 $Cb''(i,j) \leftarrow -R'(i,j)*0.169 - G'(i,j)*0.331 + B'(i,j)*0.5$
 $Cr''(i,j) \leftarrow R'(i,j)*0.5 - G'(i,j)*0.419 - B'(i,j)*0.081$

After obtaining the values in the YCbCr colorimetric system converted from the pixels of the original image and the pixels with the embedded digital watermark information that assure certain accuracy, the procedure subsequently calculates values $x(1)$, $x(2)$, and $x(3)$ from the obtained values in the YCbCr colorimetric system and then the mean x_{av} of these three values, that is, the estimated value of the watermark information x , according to equations given below (step S230):

20 $x(1) \leftarrow \{Y''(i,j) - Y(i,j)\} / \{B(i,j) - G(i,j)\}$
 $x(2) \leftarrow \{Cb''(i,j) - Cb(i,j)\} / \{R(i,j) - B(i,j)\}$
 $x(3) \leftarrow \{Cr''(i,j) - Cr(i,j)\} / \{G(i,j) - R(i,j)\}$
 $x_{av} \leftarrow \{x(1) + x(2) + x(3)\} / 3$

When the mean value x_{av} is obtained with regard to one pixel, 25 the procedure counts up the value on a counter n , which counts the number of the mean values x_{av} obtained (step S250). The above series

of processing is repeatedly carried out with regard to all the pixels (i,j) (step S240).

<Experimental Examples>

5 The following results were obtained by an experiment that embedded the digital watermark information x in the color image (256 × 256 pixels, 256 tones in each of R, G, and B) shown in Fig. 2(a) according to the embedding technique discussed above.

10 After the embedding process with the specified watermark information x, the estimated value of x was obtained according to the decoding algorithm discussed above. The frequency of appearance of each estimated value x are shown in Figs. 5(a) through 5(d). These clearly prove that the peaks of the histogram corresponding to each value of x accurately show the estimated values
15 x. The greater absolute value of x is advantageous to decrease the estimation error in the course of decoding. As clearly understood from Equation (5) given above, however, the greater absolute value of x causes the severer deterioration of the picture quality. The extremely small absolute value of x, on the other
20 hand, makes the estimation difficult. By taking account of these points, the desirable range of selection of the value x is from -1.0 to 1.0, more preferably from -0.5 to 0.5, and most preferably from -0.1 to 0.1. In order to facilitate the estimation of the value x, it is desirable to embed an identical value x in a greater
25 number of pixels. The results of Figs. 5(a) through 5(d) clearly show that the estimated value x concentrates on the vicinity of

the embedded value x . The watermark information x is accordingly estimated without any significant error.

Although the experiment embedded one value of x into the whole frame, the number of the embedded value x is not restricted to one.

5 For example, plural pieces of watermark information may be embedded in a digital color image consisting of a large number of pixels or a digital color image having a relatively monotonous variation in pixel data.

10 The following describes the evaluation results of resistance to the unexpected digital processing and the attacks of any third person against the digital color image with the digital watermark embedded therein. The description regards the experimental results of the digital color image with the embedded watermark information of $x=0.1$ that has undergone clipping, image compression (widely
15 applied JPEG compression in this experiment), StirMark attacking, and overwriting.

(1) Clipping

20 Image parts (100×100 pixels) of three areas (areas 1, 2, and 3) were clipped out of the image as shown in Fig. 6. The values x decoded from the respective clipped images according to the above algorithm are shown in Figs. 7(a), 7(b), and 7(c). As clearly understood from Figs. 7(a), 7(b), and 7(c), a clear peak is observed at $x=0.1$ in any clipped image having $1/3$ of the pixels. Namely
25 the digital watermark was decoded accurately. The technique of embedding and decoding the digital watermark according to the above

algorithm enables the embedded digital watermark information x to be accurately decoded from even the clipped part of the available color image.

5 (2) JPEG Compression

The digital image with the embedded digital watermark was subjected to JPEG compression. Figs. 8(a), 8(b), and 8(c) show the estimated values of x from the JPEG compressed image data obtained by JPEG compressing the image of Fig. 6 at the compression rates of 80%, 60%, and 40%. As clearly understood from these results, at the compression rates of 80% to over 40%, the digital watermark information x is readily decoded from the JPEG compressed image data. At the compression rate of 40% or less, however, the deterioration of the picture quality is rather significant, and the practical use is restricted to extremely special cases. The technique of embedding and decoding the digital watermark according to the above algorithm is thus applicable for general color images.

20 (3) StirMark Attacking

There is an attack upon the digital watermark called the StirMark attack and proposed by M.G. Kuhn. The image of Fig. 6 was subjected to this attacking tool StirMark. Here it is assumed that the respective parameters were set equal to default values. The technique of the embodiment enables the embedded digital watermark to be extracted from the digital color image that has undergone the attack on the digital watermark embedded in the digital

color image. Fig. 9 shows the digital watermark decoded according to the algorithm discussed above. The result of Fig. 9 clearly proves that the digital watermark information x can be accurately estimated and that the digital watermarking according to the above
5 algorithm has sufficient resistance to the StirMark attacking.

(4) Overwriting

This experiment wrote another piece of digital watermark information $x_2 = -0.1$ ($\neq x_1$) over the digital image with the embedded
10 watermark information $x_1 = 0.1$ shown in Fig. 6. Fig. 10(a) shows the watermark information extracted from the overwritten image. In this example, a peak appears at $x = 0$, which shows false watermark information. The procedure accordingly takes a difference between the overwritten image and the legal image with the embedded watermark
15 information x and decodes the difference. This enables extraction of the illegally overwriting watermark information x_2 . The result is shown in Fig. 10(b). The digital watermarking according to the above algorithm has sufficient resistance to the overwriting attack with another piece of watermark information, and enables extraction
20 of the illegally overwriting watermark information x_2 .

(5) Affine transformation

The digital watermarking technique of the embodiment embeds the watermark information in each pixel and is thus substantially
25 free from any effects of various affine transformation processes.

<General Structure of Apparatus>

The process of embedding a digital watermark in a color image and the process of decoding the embedded digital watermark are described above in the embodiment of the present invention. These processes are implemented by a digital watermark processor shown in Fig. 11. The digital watermark processor is constructed as a computer including a CPU 22, a main memory 24 including a ROM and a RAM, a frame memory 26, a keyboard 30, a mouse 32, a display unit 34, a hard disk 36, a modem 38, a scanner 39 that reads images, and a bus 40 that mutually connects the preceding elements. A diversity of interface circuits are omitted from the illustration of Fig. 11. The modem 38 is connected to a computer network via a non-illustrated communication line. A non-illustrated server on the computer network has the function as a program supply apparatus that supplies computer programs to an image processing apparatus via the communication line.

Computer programs for attaining the functions of a digital watermark embedding unit 42 and a digital watermark decoding unit 44 are stored in the main memory 24. The functions of the digital watermark embedding unit 42 and the digital watermark decoding unit 44 have already been discussed in detail.

The computer programs that attain the functions of the digital watermark embedding unit 42 and the digital watermark decoding unit 44 are provided in a specific form recorded in a computer readable recording medium, such as a flexible disk or a CD-ROM. The computer reads the computer programs from the recording medium and transfers

the computer programs to either an internal storage device or an external storage device. Alternatively the computer programs may be supplied to the computer via the communication path. A microprocessor included in the computer executes the computer programs stored in the internal storage device to attain the functions specified by the computer programs. In accordance with an alternative procedure, the computer reads the computer programs recorded in the recording medium and directly executes the computer programs.

In the specification hereof, the term 'computer' expresses the concept including a hardware device and an operating system and thus represents the hardware device working under the control of the operating system. In the case where the operating system is not required but application software alone can activate the hardware device, the hardware device itself is equivalent to the computer. The hardware device includes at least a microprocessor like a CPU and means for reading the computer programs recorded in the recording medium. The computer programs include program codes that cause the computer to attain the functions of the respective units discussed previously. Part of the functions may be attained not by the application software but by the operating system. The programs for carrying out the digital watermark embedding process and the digital watermark decoding process may be added to image processing software in the form of plug-in software programs.

Typical examples of the 'recording medium' adopted in the

present invention include flexible disks, CD-ROMs, magneto-optic discs, IC cards, ROM cartridges, punched cards, prints with barcodes or other codes printed thereon, internal storage devices (memories like a RAM and a ROM) and external storage devices of the computer,
5 and a variety of other computer readable media.

The above embodiments are to be considered in all aspects as illustrative and not restrictive. There may be many modifications, changes, and alterations without departing from the scope or spirit of the main characteristics of the present invention.

10 Industrial Applicability

The technique of the present invention is applicable for apparatuses of embedding watermark information in color images and apparatuses of electronic identification. The technique is
15 effectively applied for embedding copyright information, for personal identification in the case of electronic transactions, and for cryptography that includes apparatuses and methods of encryption, transmission, and decryption.

WHAT IS CLAIMED IS:

1. A method of embedding digital watermark information in a color image, said method comprising the steps of:

5 providing a color signal transformation matrix and an inverse color signal transformation matrix, the color signal transformation matrix transforming image data in a first colorimetric system, which expresses a predetermined color space by a combination of plural parameters, into image data in a second colorimetric system, which
10 expresses the predetermined color space by a combination of other plural parameters, the inverse color signal transformation matrix carrying out inverse of the transformation;

adjusting the color signal transformation matrix by either of adding and subtracting a digital watermark matrix to and from
15 the color signal transformation matrix, the digital watermark matrix including an arbitrary numerical value of real number x , which represents the digital watermark information, as an entry thereof and satisfying a condition that a sum of respective entries in each row and in each column is all substantially equal to zero;

20 transforming the image data in the first colorimetric system into image data in the second colorimetric system with the adjusted color signal transformation matrix; and

inversely transforming the resulting image data in the second colorimetric system, which is obtained by the transformation, into
25 the image data in the first colorimetric system with the inverse color signal transformation matrix, so as to embed the digital

watermark information into the color image.

2. An embedding method in accordance with claim 1, wherein one of the first colorimetric system and the second colorimetric system is an RGB colorimetric system using three primary colors of light as parameters, and the other of the first colorimetric system and the second colorimetric system is a YCbCr colorimetric system using a luminance signal and color difference signals as parameters.

3. An embedding method in accordance with claim 1, wherein the arbitrary numerical value of real number x is an arbitrary value in a range of not less than -0.1 and not greater than 0.1 .

4. An embedding method in accordance with claim 2, said method further comprising the step of:

carrying out either one of underflow correction and overflow correction to cause an arbitrary pixel value to be an integer within a predetermined range in the process of inversely transforming the image data in the YCbCr colorimetric system, which is obtained by the transformation with the adjusted color signal transformation matrix, into the image data in the RGB colorimetric system by means of the inverse color signal transformation matrix.

5. A decoding method to take a digital watermark out of image data with the digital watermark embedded therein, said method

comprising the steps of:

calculating a difference matrix between watermark-embedded data, which is obtained by transforming a color image with a digital watermark embedded therein into color signals in a YCbCr colorimetric system, that is, a luminance signal and color difference signals, and watermark-free data, which is obtained by transforming an original image without the digital watermark embedded therein into color signals in the YCbCr colorimetric system, that is, a luminance signal and color difference signals;

decomposing the difference matrix into respective rows and calculating an arbitrary numerical value of real number x , which is supposed to represent the digital watermark information, with regard to each row; and

estimating a mean of the numerical values of real number x calculated with regard to the respective rows as the digital watermark information.

6. A decoding method in accordance with claim 5, wherein the arbitrary numerical value of real number x , which is supposed to represent the digital watermark information, is calculated on the premise that an absolute value of a difference between entries in each row of the difference matrix is not less than a preset value.

7. A storage medium in which a program for embedding digital watermark information in a color image is stored in a computer readable manner, said program comprising:

a color signal transformation matrix that transforms image data in a first colorimetric system, which expresses a predetermined color space by a combination of plural parameters, into image data in a second colorimetric system, which expresses the predetermined color space by a combination of other plural parameters, and an inverse color signal transformation matrix that carries out inverse of the transformation;

the function of adjusting the color signal transformation matrix by either of adding and subtracting a digital watermark matrix to and from the color signal transformation matrix, the digital watermark matrix including an arbitrary numerical value of real number x, which represents the digital watermark information, as an entry thereof and satisfying a condition that a sum of respective entries in each row and in each column is all substantially equal to zero;

the function of transforming the image data in the first colorimetric system into image data in the second colorimetric system with the adjusted color signal transformation matrix; and

the function of inversely transforming the resulting image data in the second colorimetric system, which is obtained by the transformation, into the image data in the first colorimetric system with the inverse color signal transformation matrix, so as to embed the digital watermark information into the color image.

8. A storage medium in which a program for taking a digital watermark out of image data with the digital watermark embedded

therein is stored in a computer readable manner, said program comprising the functions of:

calculating a difference matrix between watermark-embedded data, which is obtained by transforming a color image with a digital watermark embedded therein into color signals in a YCbCr colorimetric system, that is, a luminance signal and color difference signals, and watermark-free data, which is obtained by transforming an original image without the digital watermark embedded therein into color signals in the YCbCr colorimetric system, that is, a luminance signal and color difference signals;

decomposing the difference matrix into respective rows and calculating an arbitrary numerical value of real number x , which is supposed to represent the digital watermark information, with regard to each row; and

estimating a mean of the numerical values of real number x calculated with regard to the respective rows as the digital watermark information.

ABSTRACT OF THE DISCLOSURE

The present invention applies a technique, which is characteristic of color images, to embed a digital watermark in a color image and decode the embedded digital watermark. The technique adjusts a color signal transformation matrix by adding or subtracting a digital watermark matrix to or from the color signal transformation matrix in the process of transforming image data of an original color image in an RGB colorimetric system into image data in a YCbCr colorimetric system with the color signal transformation matrix. The digital watermark matrix includes an arbitrary numerical value of real number x , which represents digital watermark information, as an entry thereof and satisfies a condition that a sum of respective entries in each row and in each column is all substantially equal to zero. The technique inversely transforms the image data, which is obtained by the transformation with the adjusted color signal transformation matrix, into the image data in the RGB colorimetric system by means of an inverse color signal transformation matrix. The inversely transformed image has the numerical value of real number x embedded therein as the digital watermark. The numerical value of real number x is decoded from transformed image data, which is obtained by transforming the original image into color signals in the YCbCr colorimetric system.

Fig. 1




Fig. 2 (a)

 $x = 0.1$

Fig. 2 (b)

 $x = 0.05$

Fig. 2 (c)

 $x = -0.1$

Fig. 2 (d)

 $x = -0.05$

Fig. 3




Fig. 4




Fig.5 (a)




Fig.5 (b)




Fig.5 (c)




Fig.5 (d)




Fig.6







Fig. 7 (a)*Fig. 7 (b)**Fig. 7 (c)*

Fig. 8 (a)




Fig. 8 (b)




Fig. 8 (c)




Fig. 9




Fig. 10 (a)




Fig. 10 (b)





Fig. 11



Declaration and Power of Attorney For Patent Application**特許出願宣言書及び委任状****Japanese Language Declaration****日本語宣言書**

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は、下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD OF EMBEDDING DIGITAL WATERMARK AND METHOD OF DECODING EMBEDDED DIGITAL WATERMARK

上記発明の明細書（下記の欄で×印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ _____に提出され、米国出願番号または特許協定条約
国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。

☒ was filed on April 23, 2001
as United States Application Number or
PCT International Application Number
09/830,236 and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条第56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration

(日本語宣言書)

私は、米国法典第35編第119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも1ヶ国を指定している特許協力条約365条(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

外国での先行出願

Priority Not Claimed

優先権主張なし

10-322900(P)

Japan

27/October/1998

(Number)

(Country)

(Day/Month/Year Filed)

(番号)

(国名)

(出願年月日)

☐

(Number)

(Country)

(Day/Month/Year Filed)

(番号)

(国名)

(出願年月日)

☐

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119 (e) of any United States provisional application(s) listed below.

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

私は下記の米国法典第35編第120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約第365条(c)に基づく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編第112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1章56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365 (c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application:

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私が入手した情報と私の信じることに基づく表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration

(日本語宣言書)

委任状： 私は、下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)



22434

PATENT TRADEMARK OFFICE

書類送付先：

Send Correspondence to:

Customer No. 22434

Beyer Weaver & Thomas, LLP

P.O. Box 130, Mountain View,

CA 94040 U.S.A.

直接電話連絡先： (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Steve D Beyer

(650) 961-8300

唯一または第一発明者名

Full name of sole or first inventor

Kineo Matsui

発明者の署名

日付

Inventor's signature

Date

Kineo Matsui

2/7/2001

住所

Residence

5-57, Ohtsu-machi, Yokosuka-shi, Kanagawa-ken,
239-0808 Japan

国籍

Citizenship

Japan

郵便の宛先

Post Office Address KOWA CO., LTD. 6-29, Nishiki 3-chome,
Naka-ku, Nagoya-shi, Aichi-ken, 460-0003 Japan

第二共同発明者 (該当する場合)

Full name of second joint inventor, if any

第二共同発明者の署名

日付

Second inventor's signature

Date

住所

Residence

国籍

Citizenship

郵便の宛先

Post Office Address

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)